

# WOOD FILLER

## TECHNICAL DATA SHEET

### WATERBORNE WOOD FILLER

#### PRODUCT DESCRIPTION

High quality waterborne wood filler specially designed to fill cracks, nail holes and imperfections found in hardwood floor before finishing.

#### RECOMMENDED USES

- Can be used on unfinished wood prior to medium sanding
- Designed to fill cracks, nail holes and imperfections found in hardwood floor.

#### FEATURES

- Ready-to-use
- Odor-low and non-offending
- Can be diluted with water
- Trowel applicable
- Easy to sand
- Non-shrinking
- Excellent adhesion to wood
- Absorbs stains, primer and finish at the rate as hardwood
- Available for 2 wood species: Oak, Maple - Birch
- Nonflammable

#### APPLICATION CONDITIONS\*

- Temperature between 70 °F and 77 °F (21 °C and 25 °C)
- Relative humidity between 35 % and 50 %

\* NOTE: Drying time mentioned in this document may vary depending on application conditions: lower temperature, higher humidity and greater thickness of product could slow the drying process.



Sizes	3.78 L	13.2 L
Coverage	up to 500 sq.ft.	up to 1800 sq.ft.
Product number: <b>Oak</b>	71610	71615
Product number: <b>Maple - Birch</b>	71600	71605
Quantity per skid	40	20

#### TECHNICAL DATA

Sizes available :	3.78 L and 13.2 L
Container :	Plastic container
Color :	Oak and Maple - Birch
Odor :	Low and non-offending
Coverage :	Up to 130 sq.ft. (12 m <sup>2</sup> ) / L
pH :	7,0 - 8,0
Flash point :	N.A.
Freeze / thaw stability :	Keep from freezing
Tools :	Trowel or putty knife
Shelf life :	12 months (when kept in its original container)
Tools clean up :	Water
Storage :	Dry and well ventilated
Waste disposal :	Recycle if possible (Check with local authorities)

### WATERBORNE WOOD FILLER

The information mentioned in this document is prepared to the best of our current knowledge and does not pretend to be complete. It is possible that an updated version of this document is available on our web site [finitecexpert.com](http://finitecexpert.com). In case of discrepancy, the latter takes precedence over the printed document. User is responsible to evaluate the best choice of product according to wood type and present situation before use. For more information, please consult our web site [finitecexpert.com](http://finitecexpert.com) or contact our Customer Service at 1.888.838.4449. PROFESSIONAL USE ONLY.

#### ■ FLOOR PREPARATION

##### *NEW OR RESTORED FLOOR*

Apply the wood filler with a trowel or a putty knife prior to medium sanding. Remove dust with a vacuum cleaner or dry towels.

#### ■ SANDING INSTRUCTIONS

Prepare and sand the floor according to the recommendations of the wood floor industry associations.

#### ■ PRODUCT INSTRUCTIONS

Ready-to-use. Stir to provide a homogeneous finish.

#### ■ APPLICATION GUIDELINES WITH A TROWEL

NOTE: Always do an application test on a small section to verify the compatibility and the color with the wood floor.

- 1- Sweep or vacuum the area to remove any foreign materials from cracks and voids.
- 2- Apply the wood filler with a trowel or a putty knife. Cracks must be fill as deepest as possible. Several applications may be necessary to adequately fill deeper cracks and holes.
- 3- Allow to dry completely.
- 4- Sand between layers (refer to *Sanding instructions*).
- 5- Fill any remaining cracks and holes.
- 6- Give final sanding to remove excess wood filler.

NOTE: When damp or humid conditions exist, extra drying time may be required.

#### ■ FIRST AID

Wear dust mask when sanding. Keep out of reach of children.  
EMERGENCY phone: CANUTEC (613) 996-6666.