

SURFACE TREATMENT TECHNICAL DATA SHEET

SPORTS FLOOR PREPARATION

DESCRIPTION

SURFACE TREATMENT removes oily and greasy residues on sports floor. It is used in recoating system before sanding the floor. This cleaning step reduces the risk of spread contaminants on the floor during sanding process. It optimizes the adhesion of the new coat over the existing finish and prefinished floor. SURFACE TREATMENT is part of a complete finishing system for wooden sports floor ensuring compatibility and performance.

RECOMMENDED USES

Sports floors: Basketball, volleyball, raquetball, squash, badminton, training gyms, dance floors or aerobic dance floors

FEATURES

- Removes quickly oily and greasy residues
- Ready-to-use
- Dries quickly
- Odor-low and non-offending
- NMP free and phosphate free
- Nonflammable

RECOMMENDED APPLICATORS

- Finitec applicator
- 1/8 inch (4 mm) lint free paint roller
- Sprayer

APPLICATION CONDITIONS

- Temperature between 70 °F and 77 °F (21 °C and 25 °C)
- \bullet Relative humidity between 35 % and 50 %

PRODUCT PREPARATION

Ready-to-use

NOTE: DO NOT thin. NOTE: Do not use SURFACE TREATMENT on oiled, waxed or bare wood floors.



Size	18.9 L
Coverage	up to 7500 sq.ft.
Product number	B-50022
Quantity per skid	24

TECHNICAL DATA

Size available :	18.9 L
Container:	Plastic container with spout
Color:	Colorless
Odor:	Low and non-offending
Coverage:	Up to 400 sq.ft. (35 m²) / L
pH:	12,0 ± 0,5
Density:	1,0 ± 0,2 kg/L
Freeze / thaw stability:	Stable to freeze (if frozen, thaw)
Shelf life :	12 months (when kept in its original
	container)
Tools clean up:	Water
Storage:	Between 50 °F and 85 °F (10 °C and 30 °C)
Waste disposal:	Recycle if possible
	(Check with local authorities)



1.888.838.4449finitecexpert.comLQ © 2016, Finitec Hardwood Products inc. All right reserved.

SURFACE TREATMENT

SPORTS FLOOR PREPARATION

The information mentioned in this document is prepared to the best of our current knowledge and does not pretend to be complete. It is possible that an updated version of this document is available on our web site finitecexpert.com. In case of discrepancy, the latter takes precedence over the printed document. User is responsible to evaluate the best choice of product according to wood type and present situation before use. For more information, please consult our web site finitecexpert.com or contact our Customer Service at 1.888.838.4449. PROFESSIONAL USE ONLY.

APPLICATION GUIDELINES WITH SPRAYER

NOTE: Turn off all ventilation in the gymnasium. If ventilation can not be turned off, block all ducts for a minimum of air circulation in the gymnasium.

- 1- Sweep or vacuum to remove dust, dirt and other debris. Pay special attention to corners
- 2- Spray SURFACE TREATMENT and treat the floor with a low-speed polishing machine (175 RPM) and a white pad (250 sq.ft. (23.2 m²) / side). Treat each section with SURFACE TREATMENT respecting the coverage. Do not apply an excessive amount of liquid on the floor.
- 3- Before starting another section, make sure to remove immediately any residue on the floor using wet white bath towels. Rinse the floor 1 to 2 times with warm water. Do not put dirty towels into the rinse bucket.

 $\mathsf{NOTE}:$ Overlap sections to treat the floor completely. Pay particular attention to corners.

- **4-** Once the surface is treated, allow 1 hour or until the floor is completely dry.
- 5- Sand using a 120 grit screen disc. DO NOT use steel wool. It is important to remove all traces of gloss. It is recommended to use a maroon pad (250 sq.ft. (23.2 m²) / side) after the sanding to eliminate screening marks that may appear in the final result.

 $\mathsf{NOTE:}\ \mathsf{"V"}$ grooves and hard to reach places must be hand cleaned and sanded.

6- Remove dust using a vacuum cleaner or slightly damp towels.

7- Use Finitec Expert SPORT water based recoating system (refer to *Recoating instructions for sports floor*).

8- Clean tools with water.

FIRST AID

In case of eye or skin contact, rinse well with water for 15 minutes. In case of inhalation, allow the victim to rest in a well-ventilated area. If swallowed, seek medical attention. Do not induce vomiting. Have conscious person drink several glasses of water. Keep out of reach of children. EMERGENCY phone CANUTEC (613) 996-6666.