

APPLICATION GUIDE

BEFORE YOU START

- 1- Wait a minimum of 12 hours before applying the sealer on the MicroConcrete surface.
- 2- If necessary, sand the surface of MicroConcrete with 120 / 150 grit or remove roughness with a trowel.
- 3- Clean the MicroConcrete surface with a vacuum cleaner.
- 4- Remove the masking tape (that you applied before the layer of MicroBéton) and apply a new masking tape to protect the adjacent surfaces.

STEP FOR THE MICROCONCRETE MATTE LOOK SEALER

- 1- Stir the MicroConcrete sealer and let it rest for 5 to 10 minutes.
- 2- Pour in a paint tray.
- 3- Apply with a brush or roller or **Finitec applicator**, a thin coat making sure to saturate the surface with MicroConcrete.
- 4- Wait 2 hours before applying a second coat, make sure it is dry to the touch. If necessary, you can sand the surface with 180 or 220 grit paper between coats.

SURFACES	COATS NUMBER
Decorative wall	1 to 2
Counter, furniture, table, floors	1 to 2
Showers	2

DO NOT EXCEED 12 HOURS BETWEEN COATS. DO NOT APPLY MORE THAN 2 COATS. DO NOT APPLY AN ADDITIONAL COAT IF THE SURFACE IS SATURATED.

STEP FOR THE MICROCONCRETE WET LOOK SEALER

- 1- Stir the MicroConcrete sealer and let it rest for 5 to 10 minutes.
- 2- Pour in a paint tray.
- 3- Apply with a brush or roller or **Finitec applicator**, a thin coat making sure to saturate the surface with MicroConcrete.
- 4- Wait 2 hours before applying a second coat, make sure it is dry to the touch. If necessary, you can sand the surface with 180 or 220 grit paper between coats.

SURFACES	COATS NUMBER
Decorative wall	1 to 2
Counter, furniture, table, floors	2 to 3
Showers	4

DO NOT EXCEED 12 HOURS BETWEEN COATS.

It is normal for the applicator or roller to become saturated with MicroConcrete dust after some time. Change applicators or rollers or clean them.

NEVER APPLY A MATTE FINISH SEALER OVER A WET FINISH SEALER.

APPLICATION GUIDE

MAINTENANCE

- Before the first wet cleaning, the MicroConcrete sealer needs at least 7 days to reach its complete maturation. Use Finitec cleaning products.
- Wait 7 days before using the shower.
- During the next 7 days, make sure no water is left on the surface.

DRYING TIME

Touch: between 1 and 3 hours

Recoat: 2 hours

Circulation: 12 hours

SHELFLIFE

At least 12 months when stored in its original container. Store between 15 and 30°C (60 and 86°F).

RESPONSIBILITY

It is the user's responsibility to read the instructions before using the product. Consult our website at www.finitec-inc.com or call our Customer Service Department at 1-888-838-4449 for more information.

WARRANTY

Finitec Hardwood Products Inc. certifies that the product is free from manufacturing defect. The user assumes all responsibility for use in accordance with instructions of this label. Manufacturer's responsibility is limited to replacement of the product.

FIRST AID

In case of eye or skin contact, rinse well with water for 15 minutes. In case of inhalation, allow the victim to rest in a well-ventilated area. If swallowed, seek medical attention. Do not induce vomiting. Have conscious person drink several glasses of water.