

TECHNICAL DATA SHEET

DESCRIPTION

AcoustiTECH's CERAMIC membrane is designed for ceramic or natural stone floors. This membrane composed of non-woven synthetic fibers is the most efficient in its category. Its compatibility with underfloor heating systems and its anti-fracture properties make it the #1 choice for your projects.

COMPATIBILITY

ADHESIVE

AD-280

FLOORING

Ceramic
Natural stone



THERMAL COMFORT



ACOUSTIC COMFORT



MECHANICAL STRENGTH

TECHNICAL DATA SHEET

PERFORMANCE TABLE

Test	Suspended ceiling	Structure	Flooring type	Installation	Acoustic performance	Acoustic comfort
T.181	Yes	Concrete 9"	Ceramic	Mortar	AiIC: 58	A-HiIC: 56
T.205.12	No	Concrete 8"	Ceramic	Mortar	AiIC: 56 ASTC: 60	A-HiIC: 55
T.169	No	Concrete 8"	Ceramic	Mortar	IIC: 53 STC: 59	HiIC: 53

PHYSICAL PROPERTIES

Type of fibre	Needle-punched polypropylene fibers
VOC	0 g/L
Moisture	Rot-resistant
Flammability	1 (National Fire Protection Association. NFPA)
Type of film	Non-woven polyethylene
Length	11.6 m (38.1 ft)
Width	0.8 m (31.5 in)
Thickness	3 mm ±7%
Weight	±10.4 lb (±4.7 kg)
Coverage	9.29 m ² (100 ft ²)

TECHNICAL DATA

PERM (vapor barrier) ASTM E96	N/A
R factor ASTM C518	0.439
R factor of the assembly ASTM C518	0.878 to 1.317 without floor covering
Robinson ASTM C-267	Light commercial
Grab tensile strength CAN-148.1 - no 7.3	1000 N ±5%
Grab tensile elongation CAN-148.1 - no 7.3	50% to 100%
"Mullen" bursting CAN-4.2 - no 11.1	2700 kPa ±5%
Trapezoidal tear CAN-4.2 - no 12.1	400 N ±5%
Reflectivity	70%

