

TECHNICAL DATA SHEET

DESCRIPTION

AD-860 is a fast-set, 100% solids, moisture-cure adhesive that is designed for glue-assist hardwood installation and basic wood-subfloor construction, as well as for wood-flooring repair, bonding of wood-stair nosings, wood molding, baseboards and tack-strip attachment to concrete subfloors.

COMPATIBILITY

FLOORING

Engineered wood floor
Hardwood



TECHNICAL DATA SHEET

PRODUCT PERFORMANCE PROPERTIES

Polymer type	Silane-modified
Solids content	100%
VOC	< 20 g/L
Density	1,53 g per mL (12,9 lb per U.S gal.)
Flash point	> 93 °C (200 °F)
Elongation	> 200%

SHELF LIFE AND PRODUCT CHARACTERISTICS

Shelf life	12 months when stored in original, unopened packaging at 73°F (23°C)
Consistency	Smooth paste
Color	White
Service temperature range	-23 °C to 93 °C (-10 °F to 200 °F)
Curing time	120 to 150 minutes
Storage conditions	10 °C to 32 °C (50 °F to 90 °F)



EASY TO CLEAN



LOW ODOR



FAST DRYING



CONSULT THE INSTRUCTIONS



EASY TO APPLY



HIGH PERFORMANCE PRODUCT