

Technical data sheet

Wood glue

PHYSICAL PROPERTIES

Color	Wet: white liquid / Dry: colorless
Solid content	52,0 ± 1%
pH	3
Flash point	N. A.
VOC	16 g/L
Freeze / thaw stability	Stable until -10 °C (14 °F)
Viscosity (Brookfield)	15 000 cps (5/20 rpm / 20 °C (68 °F))
Specific weight	1,095 ± 0,02

TECHNICAL DATA

Coverage	110 sq.ft. (10 m ²) / 500 mL or 370 linear foot (112,8 linear meter) / 500 mL
Assembly time	3 minutes
Cure time	2 hours
Available sizes	500 mL and 3,64 L
Shelflife	12 months (when kept in its original container)
Tools	Sponge brush or stain applicator
Tools clean-up	Soapy tepid water
Storage	Dry and well-ventilated area
Waste disposal	Recycle if possible (Consult local authorities)



FIRST AID AND WARNING

In case of contact with skin, wash immediately with mild and non-abrasive soap. If irritation persists, call a doctor. In case of contact with eyes, rinse immediately with water for at least 15 minutes, keeping eyelids open. If the person is wearing contact lenses, remove them. Do not use eye drops. If irritation persists, call a doctor. In severe cases of inhalation, move affected person in a well-ventilated area. If the victim is not breathing, give artificial respiration. Seek medical attention. If swallowed, do not induce vomiting. If the person is conscious, drink several glasses of water. Nothing by mouth to an unconscious person. Seek medical attention. KEEP OUT OF REACH OF CHILDREN.