

Technical data sheet

Water based Stain for floors and interior wood finishing

PHYSICAL PROPERTIES

Color	10 base colors available
Solid content	8 % (weight)
pH	8.0 ± 1.0
VOC	452 g/L
Flash point	N. A.
Freeze / thaw stability	Keep from freezing
Drying time (depending on conditions)	To touch: 1 hour To recoat: 3 hours for wood tones and 6 hours for white tones
Viscosity	16 to 18 seconds (Zahn #2)
Density	N.A.

TECHNICAL DATA

Coverage	Up to 125 sq.ft. (11.5 m ²) / liter (depending on conditions)
Available size	940 mL
Shelflife	12 months (when kept in its original container)
Tool	Absorbent lint-free cloth
Tools clean-up	Warm soapy water
Storage	Between 10 and 30 °C (50 and 85 °F)
Waste disposal	Recycle if possible (Consult local authorities)



FIRST AID AND WARNING

In case of eye or skin contact, rinse well with water for 15 minutes. In case of inhalation, allow the victim to rest in a well-ventilated area. If swallowed, seek medical attention. Do not induce vomiting. Have conscious person drink several glasses of water. KEEP OUT OF REACH OF CHILDREN

APPLICATION

The wood should have a moisture content between 8% and 12% before staining. After staining, it's important to wait until the moisture level returns to its initial state before applying the varnish. To know the application method, refer to the "Water-Based Stain Application Guide" by Finitec.