

Application guide

Surface preparation for wood and laminate floors

1. Vacuum.
2. Proceed to a test before using.
3. Pour the surface preparation into a paint tray. Do not pour directly onto the floor.
4. Spread on a 50 sq.ft. (5 m²) section at a time using Finitec professional applicator and let work for 5 minutes.
5. Wipe out all residues with a Finitec mop or a damp cloth and rinse the surface 2 to 3 times with warm water.
6. Repeat steps 3, 4 and 5 until the floor is free of residues. A second application may be necessary.

NOTES:

- Do not use over an oiled or waxed wood floor or on bare wood.
- Do not use the surface preparation on a new, unfinished, or porous surface, such as plywood, MDF, or HDF.

COVERAGE: up to 400 sq.ft./liter (37 m²/liter)

SHELF LIFE: at least 12 months when kept in normal storing and in its original container. Keep from freezing.

WARRANTY: Produits de Plancher Finitec Inc. certifies that this product is free from manufacturing defect. The user assumes all responsibility for use in accordance with instructions of the label. Manufacturer's responsibility is limited to the replacement of the product.

MAY IRRITATE EYES. MAY IRRITATE SKIN. DANGEROUS FUMES MAY FORM WHEN MIXED WITH OTHER PRODUCTS.

Do not mix with acidic or basic products. Do not get in eyes. Avoid contact with eyes, skin or clothing. Do not breathe fumes. Keep out of reach of children.

FIRST AID TREATMENT

Contains: Sodium Metasilicate, 2-(2-methoxyethoxy) ethanol. If swallowed, call a Poison Control Centre or a physician immediately. Do not induce vomiting. If in eyes, rinse with water for 20 minutes. Call a physician. If on skin, rinse well with water. Seek a physician if problems occur.