

Application guide

Wood stain

1. Smooth the surface with a 120 grit sandpaper (do not use steel wool).
2. Remove dust.
3. Spread a uniform coat using a brush or a stain applicator. Do not pour directly on wood.
Remove excess by wiping with a cloth.
4. Let dry for 3 hours for wood tones and 6 hours for white tones.
5. Recoated with a finish.
6. Dispose tools in fire-proof containers outdoors.

N.B.

- Do not sand Wood Stain before it is recoated with a finish.
- Must be applied on bare wood only.
- Apply only one coat of stain.
- Test on a small area to validate the color
- Color may vary according to wood species and sanding method

SHELF LIFE: The shelflife of the product is at least 12 months when kept in its original container. Store in a dry and well-ventilated area. Close tightly the container after use.

WARRANTY: Produits de Plancher Finitec Inc. certifies that this product is free from manufacturing defect. Manufacturer's responsibility is limited to the replacement of the product.

COVERAGE: 10 sq.ft. / 250 mL (1 m² / 250 mL)

**CONTENTS HARMFUL. FUMES HARMFUL. CONTENTS AND FUMES MAY CATCH FIRE.
MAY IRRITATE EYES. MAY IRRITATE SKIN.**

Do not swallow. May cause blindness if swallowed. Do not get in eyes or on skin or clothing. Do not breathe fumes. Do not smoke. Keep out of reach of children. Wear organic fumes safety mask. Wear safety glasses and rubber gloves. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. To open, push cap and turn left. Tightly close after use.

FIRST AID TREATMENT

Contains Methanol.

If swallowed, call a Poison Control Centre or doctor immediately. If person is conscious, give water to drink. Do not induce vomiting. If in eyes or on skin, rinse well with water for 20 minutes. Seek a physician. If on clothes, remove clothes. If breathed in, move person into fresh air. Seek a doctor if problem occurs.