

Technical data sheet

Tonic vinyl, ceramic, wood and laminate floors

PHYSICAL PROPERTIES

Color	Translucent white
Solid content (w/w)	20 % ± 1 %
pH	9,3 ± 0,5
Resistance to chemicals	Excellent
Resistance to abrasion (Taber test)	N. A.
VOC	240 g/L
Flash point	N.A.
Luster 60°	Semi-gloss: 40 % Satin : 17%
Freeze / thaw stability	Keep from freezing
Drying time (depending on conditions)	Light traffic: 2 to 4 hours · Furniture: 24 hours Carpets and rugs: 10 days · First wet cleaning: 10 days
Viscosity	14 to 16 seconds (Zahn #2)
Density	1,02 - 1,04 kg/L

TECHNICAL DATA

Coverage	400 sq.ft. (37 m ²) / liter (depending on conditions)
Size available	1 L
Shelflife	12 months (when kept in its original container)
Tools	Finitec applicator
Tools clean-up	Water
Storage	Dry and well-ventilated area
Waste disposal	Recycle if possible (Consult local authorities)

FIRST AID AND WARNING

Contains polymers, glycol ethers, tension-active agents. If swallowed, call a Poison Control Centre or a physician immediately. Do not induce vomiting. If in eyes, rinse with water for 20 minutes. Seek a physician. If on skin, rinse well with water. Seek a physician if problems occur. AVOID CONTACT WITH EYES OR SKIN. KEEP OUT OF REACH OF CHILDREN.

